

PAGERS



Robust, reliable, easy to program and with a full suite of message features, the W2008 is now available.

Robust Alphanumeric Pager

Comes in a robust, durable casing to ensure your product is protected and safe at all times.

Priority Override Feature

Ensures important messages can be received when they need to be.

USB Programmable

Easily programmed via USB port using Windows® software.

Multilingual Capabilities

With 8 languages available, the W2008 alphanumeric pager is ideal for use in a range of countries.

- 4 line alphanumeric
- Large font display
- Durable plastic case
- Full suite of message features
- 8 different melody alerts
- Reliable battery and back up
- Lightweight & compact

SEDCO Product Quality

SEDCO are the ISO 9001:2000 quality certified Australian manufacturer of healthcare communications.

SEDCO manufactures systems using the latest technologies ensuring they are deliverable, safe, cost effective and user friendly. SEDCO's national network delivers superior products matched with quality assured service to provide total peace of mind and the lowest total cost of ownership.

SEDCO

**4 LINE/2 LINE
ALPHANUMERIC PAGER**

MODEL: W2008

PART NUMBER

**VHF VERSION
212-0080**

**UHF VERSION
212-0090**


SEDCO

4 Line/2 Line Alphanumeric Pager

Model: W2008



SPECIFICATIONS		(Version 1.1)
Frequency Range	138-174, 405-480MHz Bands	
Channel Spacing	25KHz	
Signal Format	POCSAG	
Data Transmission Rate	512bps or 1200bps or 2400bps	
Modulation System	Carrier frequency shift keying (NRZ)	
Frequency Deviation	±4.5KHz	
Receiving Sensitivity	512bps 5uV/m, 1200bps 7uV/m, 2400bps 10uV/m	
Selectivity	60dB ±25KHz	
Image rejection	>50dB (138—480MHz); >40dB (928—932MHz)	
Spurious Rejection	>60dB (138—284MHz); >50dB (405—932MHz)	
Frequency Stability	±10ppm(138-284 MHz), ±5ppm(406-480 MHz), ±3ppm(928-932MHz)	
Tone Alert Output	More than 75dB(SPL) 10cm, frequency 2731Hz	
Operating Voltage	1.0V (min)	
Operating Temp. Humidity	-10° C to 40° C, 95% (at 40° C)	
Storing Temp. Humidity	-10° C to 70° C, 95% (at 40° C)	

FEATURES	
Message storage Capacity	19 Personal messages, 16 Mail drop messages, each 512 ASCII
Address Code	8 paging addresses , last 4 addresses can be programmed personal or maildrop
Display Format	20 chars. x 4 lines + 1 line ICONS, or 20 chars x2 line+1line icon, user selectable
Time/Date Display	Real time with date displayed in 24 or 12 hours format
In Range Indication	If pager is within range of reception, “ Y ” will not be displayed
Low Voltage Alert	Display will show “  ” indicating low voltage
Backlight	Backlight can be turned on manually under dim environment
Message Received Time	Message receiving time is memorized and displayed together
Message protection	16 messages
Message Deletion	Self messages can be deleted individually; self messages and mail drop can be deleted all.
Unread message	ICON flashing to remind unread message and audible alert (optional)
Duplicate Message	Duplicate message indication provided
Melody Alert	8 different melody alerts, continuous audible alert (selected by programming software)
Alert Time	Can be programmed
Vibration Alert	Build-in vibrator will be activated automatically to indicate receptions of calls
Silent Alert	Pager can receive message without vibration, tone alert
Alarm	Built-in alarm function at preset time
Language	English, Spanish, French, Italian, German, Portuguese, Danish. Swedish
Battery	One “AA” battery (1.5V) Battery provided.
Battery Life	512bps, 950 Hours (Alkaline battery), 1200bps, 800 Hours (Alkaline battery)
Battery Back-up	Over 30 seconds (when the battery is replaced)
Weight	90 gms. (including battery)
Size	80.5x54.4x24mm (without holster)